

WL250 CT

Performance worthy of an encore and functional design for the workplace

Refreshing water for any working environment

With a choice of hot or cold, the WL250 is a popular choice for offices and factories where great quality water is required.

Advanced technology

The WL250 features three core technologies:



High performance filtration

Our filters are certified to stringent standards by IAPMO R&T, carrying the Water Quality Platinum Seal, meaning they offer the best possible filtration. Multi-stage filtration removes common water contaminants and chlorine to dramatically improve water taste and odor.



In-tank UV sanitization

Our in-tank UV technology acts against waterborne microorganisms and bacteria, dispensing great quality water, glass after glass.



BioCote[®] product protection

The key plastic surfaces surrounding the dispensing area are infused with BioCote[®], a silver ion additive that inhibits the growth of odor and stain causing microbes, such as bacteria and mold.

*BioCote[®] silver ion technology protects surfaces from odor- and stain-causing microbes. BioCote[®] does not protect users or others against bacteria, viruses, germs or other disease causing organisms. This technology is not a substitute for good cleaning practices.

Simply great, clear water**

Free from fluoride, free from chlorine, and free from water-borne tastes and odors. (Dependent on filters type and water conditions.)

**Filtration results based on the use of RO, GAC, CBC, or sediment filters.



WL250 CT water dispensing unit

Features

In-tank UV technology is highly effective against germs and bacteria. A UV lamp treats the water stored in the reservoir for fast, reliable, and easy water purification

Removable drip tray to collect accidental spillage

Sleep mode to conserve energy

BioCote® treated dispensing area to protect it from odor and stain causing microbes

Thermal overload protection

Easy connection to the existing water supply

Leak detection for peace of mind

Water options



Number of users: 10-30

Technical specifications

Types available: **Countertop**

Dimensions: **13.6" (W) x 17.7" (H) x 14.4" (D)**

Dispensing area height: **8.5"**

Weight (Countertop): **42lbs**

Standard filtration recommended: **Sediment, GAC, CBC with lead and cyst removal (dependent on local water conditions)**

Storage capacity

Cold tank: **2 liters (countertop)**

Hot tank **1.6 liters**

Drip tray capacity: .4 US gal

Compressor: 120V/60Hz

Water temperatures settings

Cold: **37°-54°F** Hot: **187°F**



Contact us today

Purlogix
3175 Bass Pro Drive, Grapevine, TX 76051

www.purlogix.com
(800) 288-1891 | dealerorders@purlogix.com

Tested and certified



Certified by IAPMO R&T to NSF/ANSI 61, CSA B483.1 and NSF/ANSI 372 for lead free compliance.